

# Road Service Co., Ltd. is a manufacturer and distributor of tow trucks.

*The body manufactured in aluminium is light-weighted, rust resistant and strong.  
We have 30 years of experience in wrecker service business.*

## Sales Performance

Road Service has sold over 200 trucks (as of March 2018) in Japan since starting sales in 2008.

## Sales Performance



## Work experience



### Note

All the performance abilities indicated in this catalogue is that of the equipment itself, and the actual performance may vary depending on the truck that the equipment is installed on. Main specifications and equipment may change without prior notice.

 **Road Service Co., Ltd.**

171-1 Nabano, Aioi, Hyogo, 678-0011, Japan

■ H P <http://www.jroad.info>  
■ TEL +81-791-23-6166  
■ FAX +81-791-23-6882  
■ MAIL [okumoto@jroad.info](mailto:okumoto@jroad.info)

Outstanding Skills and Reliable Confidence



# ROAD SERVICE



**Road Service Co., Ltd.**



# The Ultimate Cost Performance Rotational Tow Truck

*360° Rotational Tow Truck, 2 3-stage winch boom on 10 t winch.  
Shows maximum strength with double rotational motor.*



## QZF10

**QZF10**  
Large-size wrecker equipment

The patented under lift keeps the front wheel on the ground and shows its maximum performance when towing. Slimly designed, it boosts up the efficiency in any work site and will definitely satisfy you. The bus attachment makes it possible to tow trailers to large-sized tour buses.

The pictures shown are for illustrative purposes only.

### Winch Boom

3-stage	5,030mm to 10,780mm
Rotational Angle	360°
Rotational Equipment	2 hydraulic motor
Boom Hoisting Angle	55°
Winch	2×10t (18mm×70m)
Deck Mount Winch	1×10t (18mm×35m)

### Under Lift

3-stage	1,920mm to 3,510mm
Tilt	13° to -15°
Thickness	212mm

Equipped with front & rear outrigger, standard attachment included (including bus attachment), radio control included (manufactured in Germany by HBC-radiomatic)



*World's first 360° rotational winch boom.  
Any work is possible with the 3-stage long boom and double wrench.  
The under lift tows from light passenger vehicles to small-sized trucks.*



## QZF3

**QZF3**  
Small-sized wrecker equipment

Independent type towing equipment with 3-stage winch boom and 2-stage under lift. The under lift is slim and wide. The boom is 360° rotational boom with double winch shows its maximum power in difficult cases such as rollover or car fall accidents. Both the winch boom and the under lift are controlled remotely. Can be installed on chassis WB 2,500 mm to 3,400 mm.

The pictures shown are for illustrative purposes only.

### Winch Boom

3-stage	2,520mm to 5,320mm
Rotational Angle	360°
Boom Hoisting Angle	60°
Winch	2×4t
Winch wire	10mm × 35m

### Under Lift

2-stage	1,225mm to 1,930mm
Tilt	15° to -15°

